

STOP LEAK (1 l bottle)

**Sealing fluid with inorganic base designed for sealed heating circuits.**

Stop Leak is a fluid designed to seal minor leaks in heating systems in metal or plastic, for leaks up to 50 l per 24 h. When dosed into a heating system, it starts sealing slowly the microleaks caused by corrosion or defect connections exploiting contact with oxygen from outside the leak.

**Instructions for use:**

1. Shake well prior to use!
2. Dose 1 litre of the agent per every 100/150 l water.
3. Let it circulate in a heating system until the leaks stop completely. To seal minor leaks, 2-3 hours will be sufficient.
4. In case of bigger leaks, sealing may last even more than 7 days.
5. During the application, strainers from filters shall be removed. The system need not be drained.
6. Presence of antifreeze and anticorrosion additives, salts and other additives may have disruptive influence on the efficiency of the agent.

**Storage:**

Kepp in a dry place.

Protect from frost.

**The product is intended for professional use.**

**Dangerous substances:** isopropyl-alcohol - CAS: 200-661-7 (5-10%)

**EUH210** MSDS is available upon request.

**R phrases:**

R11 Highly flammable; R36 Irritating to eyes; R67 Vapours may cause drowsiness and dizziness

**H phrases:**

H225 Highly flammable liquid and vapour; H319 Causes serious eye irritation; H336 May cause drowsiness or dizziness.

**Manufacturer:** Manta Ecologica S.r.l.,Italy

**Distributor:**

The logo for Regulus, featuring the word "Regulus" in a stylized, red, serif font with a red swoosh underline.

**REGULUS spol. s r.o.**

Do Koutů 1897/3

143 00 Praha 4

<http://www.regulus.eu>

E-mail: [sales@regulus.eu](mailto:sales@regulus.eu)